AMENDMENT UNDER 37 C.F.R. § 1.111

Application No.: 10/536,752

Attorney Docket No.: Q88220

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (currently amended): A bending durability prediction method of predicting a bending

durability of a plurality of wires laid at a predetermined bend, and of a bend protection member

attached at the bend to protect the plurality of wires, by using an infinite element method, the

bending durability prediction method comprising:

a setup step of setting up the plurality of wires, the bend protection member, an

atmosphere temperature, pre-bending initial shapes for the wires and the bend protection member

and final bent shapes for the wires and the bend protection member;

an infinite element model preparation step of preparing infinite element models for the

plurality of wires and the bend protection member;

a stress calculation step of calculating stress, for each of infinite elements of the infinite

element models, produced by bending the infinite elements from the initial shape to the final bent

shape;

a maximum stress search step of searching, among the stresses obtained at the stress

calculation step, for the maximum stress for each of the plurality of wires and the bend

protection member;

a prediction function acquisition step of obtaining prediction functions for the wires; and

the bend protection member and at the atmosphere temperature designated setup at the setup step;

Application No.: 10/536,752

a predicting step of referring to the prediction functions obtained at the prediction

function acquisition step, obtaining numbers of bendings for endurance which correspond to the

maximum stresses for the wires and the bend protection member, and identifying the smallest

number of bendings for endurance; and

an output step of outputting the smallest number of bendings obtained at the predicting

step.

2. (original): The bending durability prediction method according to claim 1 further

comprising:

a specifying step of specifying a position on the wires or the bend protection member

corresponding to the smallest number of bendings for endurance,

wherein the position specified at the specifying step is output at the output step.

3. (original): The bending durability prediction method according to claim 1, wherein as

the prediction function, a curve is employed that represents a lower confidence interval relative

to a modular regression function that is statistically obtained based on data on the stresses and

the number of bendings for endurance which are acquired under a plurality of typical atmosphere

temperatures.

4. (original): The bend durability prediction method according to claim 1, further

comprising:

Application No.: 10/536,752

a wire arrangement step of arranging, innermost at the bend, a thickest wire of all the plurality of wires.

5. (original): The bend durability prediction method according to claim 1, further

comprising:

a storing step of previously storing stress tables which represent minimum stresses according to which it is assumed that the plurality of wires and the bend protection member will

be damaged;

a stress table reading step of reading stress tables corresponding to the plurality of wires,

the bend protection member and the atmosphere temperature designated in the setup step; and

a damaged member specifying step of specifying the wire or the bend protection member

that is first damaged, while referring to the stress tables that are read at the stress table reading

step and the individual maximum stresses that are found at the maximum stress search step for

the wires and the bend protection member,

the output step outputs information specifying the wire or the bend protection member

that is first damaged.

6. (original): A bending durability prediction method of predicting a bending durability

of a plurality of wires laid at a predetermined bend, and of a bend protection member attached at

the bend to protect the plurality of wires by using an infinite element method, the bending

durability prediction method comprising:

Application No.: 10/536,752

a storing step of previously storing stress tables which represent minimum stresses according to which it is assumed that the plurality of wires and the bend protection member will be damaged;

a setup step of setting up the plurality of wires, the bend protection member, an atmosphere temperature, pre-bending initial shapes for the wires and the bend protection member and final bent shapes for the wires and the bend protection member;

an infinite element model preparation step of preparing infinite element models for the plurality of wires and the bend protection member;

a stress calculation step of calculating stress, for each of infinite elements of the infinite element models, produced by bending the infinite elements from the initial shape to the final bent shape;

a maximum stress search step of searching, among the stresses obtained at the stress calculation step, for the maximum stress for each of the plurality of wires and the bend protection member;

a stress table reading step of reading stress tables corresponding to the plurality of wires, the bend protection member and the atmosphere temperature designated in the setup step;

a damaged member specifying step of specifying the wire or the bend protection member that is first damaged, while referring to the stress tables that are read at the stress table reading step and the individual maximum stresses that are found at the maximum stress search step for the wires and the bend protection member; and

an output step of outputting information specifying the wire or the bend protection member that is first damaged.

Application No.: 10/536,752

7. (original): The bend durability prediction method according to claim 6, further

comprising:

a wire arrangement step of arranging, innermost at the bend, a thickest wire of all the

plurality of wires.

8. (original): A bending durability prediction apparatus for predicting a bending

durability of a plurality of wires laid at a predetermined bend, and of a bend protection member

attached at the bend to protect the plurality of wires by using an infinite element method, the

apparatus comprising:

a setup unit for setting up the plurality of wires, the bend protection member, an

atmosphere temperature, pre-bending initial shapes for the wires and the bend protection member

and final bent shapes for the wires and the bend protection member;

an infinite element model preparation unit for preparing infinite element models for the

plurality of wires and the bend protection member;

a stress calculation unit for calculating stress, for each of infinite elements of the infinite

element models, produced by bending the infinite elements from the initial shape to the final bent

shape;

a maximum stress search unit for searching, among the stresses obtained by the stress

calculation unit, for the maximum stress for each of the plurality of wires and the bend protection

member;

Application No.: 10/536,752

a prediction function acquisition unit for obtaining prediction functions for the wires, the

bend protection member and the atmosphere temperature designated by the setup unit;

a predicting unit for referring to the prediction functions obtained by the prediction

function acquisition unit, obtaining numbers of bendings for endurance which correspond to the

maximum stresses for the wires and the bend protection member, and identifying the smallest

number of bendings for endurance; and

an output unit for outputting the smallest number of bendings obtained by the predicting

unit.

9. (original): A computer readable recording medium storing a program for predicting a

bending durability of a plurality of wires laid at a predetermined bend, and of a bend protection

member attached at the bend to protect the plurality of wires by using an infinite element

method, the program causing a computer to function as:

a setup unit for setting up the plurality of wires, the bend protection member, an

atmosphere temperature, pre-bending initial shapes for the wires and the bend protection member

and final bent shapes for the wires and the bend protection member;

an infinite element model preparation unit for preparing infinite element models for the

plurality of wires and the bend protection member;

a stress calculation unit for calculating stress, for each of infinite elements of the infinite

element models, produced by bending the infinite elements from the initial shape to the final bent

shape;

Application No.: 10/536,752

a maximum stress search unit for searching, among the stresses obtained by the stress calculation unit, for the maximum stress for each of the plurality of wires and the bend protection member:

a prediction function acquisition unit for obtaining prediction functions for the wires, the bend protection member and the atmosphere temperature designated by the setup unit;

a predicting unit for referring to the prediction functions obtained by the prediction function acquisition unit, obtaining numbers of bendings for endurance which correspond to the maximum stresses for the wires and the bend protection member, and identifying the smallest number of bendings for endurance; and

an output unit for outputting the smallest number of bendings obtained by the predicting unit.

10. (new): A bending durability prediction method comprising:

preparing infinite element models for materials;

calculating stress, for each infinite element of the infinite element models, produced by bending the infinite elements from an initial shape to a final bent shape;

searching, among the calculated stresses, for maximum stress for each of the materials; obtaining a prediction function for the materials;

obtaining numbers of bendings which correspond to the maximum stresses for the materials;

identifying the smallest number of bendings producing failure; and outputting the smallest number of bendings identified.

Application No.: 10/536,752

11. (new): The bending durability prediction method of claim 10, wherein the materials

comprise a plurality of wires.

12. (new): The bending durability prediction method of claim 11, wherein the materials

further comprise a bend protection member.

13. (new): The bending durability prediction method of claim 12, further comprising

setting an atmosphere temperature.

14. (new): The bending durability prediction method of claim 10 further comprising:

specifying a position on the materials corresponding to a smallest number of bendings

producing failure; and

outputting the position specified.

15. (new): The bending durability prediction method of claim 10, wherein the prediction

function employs a curve that represents a lower confidence interval relative to a modular

regression function that is statistically obtained based on:

data regarding stresses; and

a number of bendings producing failure acquired under a plurality of typical atmosphere

temperatures.

Application No.: 10/536,752

16. (new): The bend durability prediction method of claim 11, further comprising arranging the plurality of wires in a bundle such that a thickest wire is the center wire of the

bundle.

17. (new): The bend durability prediction method of claim 10, further comprising:

storing stress tables which represent minimum stresses at which the materials will be

damaged;

reading the stress tables;

specifying a material that is damaged first by using the stress tables and the maximum

stresses for the materials; and

outputting information specifying the material that is damaged first.

18. (new): The bending durability prediction method of claim 17, wherein the materials

comprise a plurality of wires.

19. (new): The bending durability prediction method of claim 18, wherein the materials

further comprise a bend protection member.